

M22 403 Quarter Turn Latches

Descripción

Quarter turn latches far doors with a thickness between 6 and 57mm (see R). Designed far use in harsh climate conditions or when IP-rating is required.


AGA supplies as standard L=18mm, R=6 or 8mm, with Z-150 cam and without key except in the model 400, which is supplied with 59DP or 8705 key model (page 9). Further measurements upan request.

| KEY FORM | Triangular 8 mm | | | |
|-------------------|--|--|--|--|
| MATERIAL | Black polyamide (fireproof) | | | |
| FINISH (zamak) | - | | | |
| FEATURES | L = 18 mm / R = 6 mm | | | |
| WEIGHT(grs) | 46 | | | |
| LOCKING DIRECTION | 90° Left/Right | | | |
| IP-RATING | - | | | |
| ACCESORIES | M22 Nut, M22 metallic washer, M22 plastic washer | | | |
| KEY | 3018T | | | |

Fotos









Otros Accesorios:



| | | ≥ 8 | | | | | | | |
|---|------|------|------|------|------|------|------|------|---|
| z | Z150 | Z151 | Z152 | Z153 | Z157 | Z158 | Z159 | Z160 | |
| н | 47 | 52 | 57 | 62 | 47 | 47 | 47 | 47 | 4 |
| G | - | - | - | - | 5 | 10 | 15 | 20 | |

